

Portable Vaporizers

Modular, Skid Mounted Vaporization Systems

Simple, Reliable, Easy To Operate

ReGasPro 55 & 74

Introducing advanced cryogenic vaporizers, expertly designed to simplify operation and integrate seamlessly with cryogenic tanks for reliable and efficient regasification of cryogenic liquids to gas. Units are capable of vaporizing a vast variety of cryogenic liquids including LOX, LIN, LAR, LNG.

Crafted for optimal efficiency and performance, our vaporizers offer dependable, cost-effective operation and can be customized with auxiliary features to fit your specific needs.

Technical Description:

- ★ **Service:** LNG, LN2, LOX, LAR
- ★ **Design Pressure:** Up to 700 PSI
- ★ **Design Temperature:** -320 F / 196°C
- ★ **Material:** Aluminum tubing welded to ASME B31.3 code
- ★ **Inlet, Outlet:** Class 300 RF Flange
- ★ **Offered in Rating:** 55,000 SCFH & 74,000 SCFH*
- ★ **Locking Mechanism:** Standardized ISO Connections
- ★ **Base:** Galvanized Steel Frame
- ★ **Handling:** Forklift / Small crane

Benefits:

- ✓ Expandable, Modular-based (20-foot skids)
- ✓ "Plug and Play" less than 1 hours to start operating
- ✓ Simple Assembly / No Welding Required
- ✓ No External Power Source Required
- ✓ No Crane Required / Movable with 10K Forklift

Features:

- ✓ Hybrid Fins Designed for Maximum Surface Area
- ✓ Customized Outfit Available to Meet Project Needs
- ✓ Galvanized skid-based install on chassis or dropped on surface
- ✓ Designed to operate in series or to alternate between vaporizers
- ✓ Stackable with No Crating Required (offered in 40-ft Frames)



* Note: Flow Rate on N2; 8 hrs. per day; 150 psi inlet at 70~f

ReGasPro – simply reliable vaporizers to go!

Most Popular Models:

ReGasPro 55

Flow Rate: 55,000 SCFH / Up to 700 PSI

Skid Dimensions:

20 ft long (3.5 ft for Auxiliary equipment)
8.4 ft wide, 8.4 ft height

Skid weight: Roughly 6,000 lb.

ReGasPro 74

Flow Rate: 74,000 SCFH / Up to 700 PSI

Skid Dimensions:

20 ft long x 8.4 ft wide x 8.4 ft height

Skid weight: Roughly 6,500 lb.



55,000 SCFH On 20 ft frame



Dual 55,000 can run separate or continuous



Quick Locking Mechanism for trailer / mounting



Class 300 RF Flange

- ✓ All other products and lesser inlet pressures would require sizing.
- ✓ Both manual and automatic switch over systems are available to allow continuous duty 24/7 operation
- ✓ Frames: 10 ft - 20 ft – 40 ft frames fit on standard ISO chassis. 40 ft units will be in steel frame

Fast and steady, gas to go—trust the power of ReGasPro!

📍 Manufactured in Dallas, Texas USA

✉ info@gasequipmentforsale.com

☎ 1 (800) 716-6747



Trailer mount option



4'x 8' steel deck for auxiliary items



74,000 SCFH on 20 ft frame



108,000 SCFH on stackable 40 ft frame



FOR MORE DETAILS PLEASE CONTACT US:

✉ info@gasequipmentforsale.com

☎ 1 (800) 716-6747

MANUFACTURED IN:

Dallas, Texas

Note: The performance of ambient air vaporizers is subject to many factors. These include flow, duty cycle, ambient temperature, relative humidity, freeze period, altitude, wind, solar radiation, operating pressure and proximity to adjacent structures. The effects of average solar and wind conditions are not included in the above ratings.

Ratings are based on mean ambient conditions of 70°F (21°C) and 70% relative humidity. Special conditions may vary considerably for a particular application, thereby affecting performance.

Call us for your specific requirements. Over \$1 Million in vaporizer immediately available! Valves, Piping, Regulators, Hoses in stock to support your project.

From liquid to flow, with ReGasPro, MCFH available up to 74!

📍 Manufactured in Dallas, Texas USA

✉ info@gasequipmentforsale.com

☎ 1 (800) 716-6747

